


Elcometer 3508 & 3560 4 Gap Applicator with Reservoir



Elcometer 3508 & 3560 4 Gap Applicator with Reservoir

Elcometer 3508 & 3560 4 Gap Applicator with Reservoir A simple gauge with a single reservoir

A simple gauge with a single reservoir allowing the user to generate 4 different values of thickness of coating.

These stainless steel applicators are made with 4 straight spreading edges of fixed film gaps.

The Elcometer 3508 4 Gap Applicator with 2 reservoirs has been designed specifically for the generation of test samples for use with the Elcometer 1720 Abrasion, Scrubbing and Washability Tester.

Film Application & Test Charts

For numerous products such as paint, ink, varnishes, glue and cosmetics, the reliability of many laboratory tests is directly related to the quality of the samples prepared from it

It is absolutely essential that any measurements made on such coatings, whether for the purpose of describing their appearance or their physical properties (colour, gloss, hiding power, drying time, etc), are made on the basis of uniform and comparable samples with precisely controlled thickness.

In order to meet such specific demands, Elcometer has a wide range of high quality, high precision film applicators and motorised film applicators for greater repeatability and reproducibility when undertaking a large number of sample tests.

Elcometer also offer a wide range of Leneta Test Charts – the market standard – to meet all your specific requirements

At a glance

- 4 thickness values in one gauge.
- Single or double reservoir option.
- Can be used for the preparation of samples for the Elcometer 1720 Abrasion and Washability Tester.

Can be used in accordance with:				
ASTM D 3022	ASTM D 823			
FTMS 141a M2161	FTMS 141a 2162			

Model	Number of Gaps	Film Gaps		Film Width		Part Number			
		μm	mils	mm	inches	Metric	Imperial		
Elcometer 3560/1	4	30, 60, 90, 120	1, 2, 3, 4	60	2	K0003560M201	K0US3560M201		
Elcometer 3560/2	4	50, 100, 150, 200	2, 4, 6, 8	60	2	K0003560M202	K0US3560M202		
Elcometer 3508	4	100, 150, 200, 250	4, 6, 8, 10	2 x 50	2 x 2	K0003508M001	K0US3508M001		
Packing List	Elcometer	Elcometer Film Applicator, Storage case & Operating instructions							

data sheet

Related products



Elcometer 3700

Similar in operation and design to the Elcometer 3600, this unit has the added advantage of a reservoir to store the coating.



Elcometer Leneta test



Elcometer 1720

Charts, from plain white to those having different patterns of black and white. Produced from high quality, non-fluorescent paper, free of optical brighteners that may affect colour measurements, Leneta Test Charts are the market standard in today's coatings industry.

Elcometer supply a wide range of Leneta Test

This robust and easy to use Abrasion Tester is extremely flexible and is designed to test the washability, brushability and abrasion resistance of a wide range of materials, including paint, lacquers, inks, coatings and much much more. Unlike most washability testers, this unit is easy to set up and is available as either a 2 or 4 station model and can measure on flat or curved surfaces.

elcometer

ENGLAND

Elcometer Instruments Ltd Edge Lane Manchester M43 6BU

Tel: +44 (0) 161 371 6000 Fax: +44 (0) 161 371 6010 e-mail: sales@elcometer.com www.elcometer.com

USA

Elcometer Instruments Inc 1893 Rochester Industrial Drive Rochester Hills Michigan 48309

Tel: +1 248 650 0500 Toll free: 800 521 0635 Fax: +1 248 650 0501 e-mail: inc@elcometer.com www.elcometer.com

CANADA

Elcometer Canada Ltd PO Box 622, 401 Ouelette Avenue Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500 Toll Free: 800 521 0635 Fax: +1 248 650 0501 e-mail: ca_info@elcometer.com www.elcometer.com

ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd 896 Dunearn Rd Sime Darby Centre #3-09 Singapore 589472, Republic of Singapore

Tel: +65 6462 2822 Fax: +65 6462 2860 e-mail: asia@elcometer.com www.elcometer.com

BELGIUM

Elcometer SPRL Rue Vallée 13 B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10 Fax: +32 (0)4 374 06 03 e-mail: be_info@elcometer.be www.elcometer.be

FRANCE

Elcometer SARL BP 8-Bou 60 Rue de la Petite Levée 45430 Chécy

Tel: +33 (0)2 38 86 33 44 Fax: +33 (0)2 38 91 37 66 e-mail: fr_info@elcometer.fr www.elcometer.fr

GERMANY

Elcometer Instruments GmbH Himmlingstraβe 18 D-73434 Aalen

Tel: +49 (0) 7366 91 92 83 Fax: +49 (0) 7366 91 92 86 e-mail: de_info@elcometer.de www.elcometer.de