

elcometer®  
inspection equipment



**Elcometer 415**  
Industrial Paint & Powder  
Thickness Gauge

**Elcometer 415**

**Industrial Paint & Powder Thickness Gauge**

The new Elcometer 415 Industrial Paint & Powder Thickness Gauge provides simple, fast and accurate coating thickness measurements on smooth and thin industrial paint and powder coatings.

**STANDARDS:**  
 AS2331.1.4, AS/NZS 1580.108.1, ASTM B 499, ASTM D 1186, ASTM D 1400, ASTM D 7091, ASTM E 376, BS 3900-C5-6A, BS 3900-C5-6B, BS 5411-11, BS 5411-3, BS 5599, DIN 50981, DIN 50984, ECCA T1, EN 13523-1, ISO 2360, ISO 2808-12, ISO 2808-6A, ISO 2808-6B, ISO 2808-7C, ISO 2808-7D, JIS K 5600-1-7, NF T30-124



**360°  
 AUTO  
 ROTATING  
 SCREEN**

Large easy to read values in microns or mils

1 point & 2 point calibration ensures accuracy on smooth & thin coated substrates

Easy to use, ergonomic design provides maximum comfort for continuous use

Incredibly fast (60+ readings per minute), reducing inspection times, increasing productivity

Measures cured paint & powder coatings up to 1000µm (40mils)

Auto rotating large colour display provides clear visibility whatever the angle of measurement

Scratch, solvent & powder resistant display

Transfer live data via USB or Bluetooth® to ElcoMaster® for instant report generation

Rugged & resistant to powder coatings ingress equivalent to IP64

Automatically switches between ferrous & non-ferrous substrates<sup>1</sup>

new

new



Ideal for measuring dry film thickness on thin coated substrates.



360° auto rotating display for a clear reading at any measurement angle, on the production line or QA station.



Transfer live data via Bluetooth®<sup>2</sup> to PC, Android™ or iOS mobile devices.

<sup>1</sup> Elcometer 415 FNF models <sup>2</sup> Elcometer 415 Model T

**Industrial Paint & Powder Thickness Gauge**

**Elcometer 415**

**Key Features Explained**

**The new Elcometer 415 doesn't just take a thickness measurement**

In addition to the coating thickness, the new Elcometer 415 displays the key statistical values required to assess the overall industrial finishing; number of readings (n), average ( $\bar{x}$ ), lowest (Lo) and highest (Hi) paint thickness.

**Stay accurate with simple calibration**

This new, easy to use, Elcometer 415 has 1 point & 2 point calibration, ensuring accurate measurements on smooth & thin industrial paint & powder coated surfaces.

**Each gauge is designed to last**

Robust, durable & powder resistant, the new Elcometer 415 is available with a 2 year\*\* manufacturer's warranty; giving you peace of mind.

**Seamlessly connect to any PC, Android™ or iOS mobile device**

As each measurement is taken the new Elcometer 415 instantly transmits the thickness values via USB or Bluetooth® 2 to your PC or mobile device using ElcoMaster® or your own software application.



**ElcoMaster®**  
 data management software



**360°  
 AUTO  
 ROTATING  
 SCREEN**

Bluetooth®



Download on the **App Store**

ANDROID APP ON **Google play**

**Android™**

Made for **iPod iPhone iPad**

compatible with **ElcoMaster®**

\*\* Elcometer 415 gauges are supplied with a one year warranty against manufacturing defects. The warranty can be extended to two years via [www.elcometer.com](http://www.elcometer.com)

# Dry Film Thickness - Digital

## Elcometer 415

## Industrial Paint & Powder Thickness Gauge®

### Technical Specification

Model	Model B	Model B	Model T	Model T	Certificate
Part Number	A415CFBI	A415CFNFBI	A415CFTI	A415CFNFTI	●
Built in probe type	Ferrous	Ferrous/ Non Ferrous	Ferrous	Ferrous/ Non Ferrous	
Live data output	USB	USB	Bluetooth® & USB	Bluetooth® & USB	
On screen statistics	Number of readings (n), Average (mean $\bar{x}$ ), Lowest reading (Lo), Highest reading (Hi)				
Reading rate	60+ readings per minute		Measurement Range: 0 - 1000 $\mu$ m (0 - 40mils)		
Accuracy <sup>1</sup>	$\pm 1-3\%$ or $\pm 2.5\mu$ m ( $\pm 0.1$ mil)				
Resolution	0.1 $\mu$ m: 0 - 100 $\mu$ m; 1 $\mu$ m: 100 - 1000 $\mu$ m (0.01mil: 0 - 5mils; 0.1mil: 5 - 40mils)				
Minimum Substrate Thickness <sup>2</sup>	Steel: 800 $\mu$ m (30mils)		Aluminium: 300 $\mu$ m (12mils)**		
Operating Temperature	-10 to 50°C (14 to 122°F)		Relative Humidity (RH): 0 to 95%		
Power Supply	2 x AA Batteries or via USB Cable ( <i>rechargeable batteries can also be used</i> )				
Battery Life <sup>3</sup>	Alkaline: Approx. 16 hours		Lithium: Approx. 24 hours		
Gauge Dimensions (h x w x d)	14.1 x 7.30 x 3.70cm (5.55 x 2.87 x 1.46")				
Gauge Weight	156g / 5.5oz ( <i>including batteries</i> )				

### Packing List

Elcometer 415 gauge, 2 x AA batteries, steel & aluminium check pieces\*, foil set, wrist strap, impact resistant carry case, screen protector†, calibration test certificate, operating instructions, USB cable†, ElcoMaster CD† & 2 year warranty extension card

### Accessories

T99916925	Calibration Check Piece; Steel (Ferrous)	T99022255-1C	Certified Foil Set; 0 - 1000 $\mu$ m (0 - 40 mils)
T99916901	Calibration Check Piece; Aluminum (Non-Ferrous)	T99921325	USB Cable
T99022255-1	Foil Set; 0-1000 $\mu$ m (0 - 40mils)	T99922341	Self Adhesive Screen Protectors (Pack of 10)

<sup>1</sup> Whichever is the greater

<sup>2</sup> For specified accuracy

<sup>3</sup> Rechargeable batteries may differ

† Model T

\* F models: steel check piece; FNF models: steel & aluminium check pieces

\*\* FNF models

● Calibration Certificate supplied as standard.

Elcometer 415 Model T: Made for iPhone 6 Plus, iPhone 6, iPhone 5s, iPhone 5c, iPhone 5, iPhone 4s, iPhone 4, iPad Air 2, iPad mini 3, iPad Air, iPad mini 2, iPad (3rd and 4th generation), iPad mini, iPad 2, and iPod touch (4th and 5th generation). "Made for iPod," "Made for iPhone," and "Made for iPad" mean that an electronic accessory has been designed to connect specifically to iPod touch, iPhone, or iPad, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Please note that the use of this accessory with iPod touch, iPhone, or iPad may affect wireless performance. iPad, iPhone, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a trademark of Apple Inc., registered in the U.S. and other countries.

Suitable for mobile devices running Android software version 2.1 and upwards. Android is a trademark of Google Inc.